553480240040

General purpose relay 7 - 10 A



This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

Technical description:
Industrial relay, Plug-in socket version, 4 pole, CO (nPDT), 7 A, AgNi, AC coil, 24 V, operating from 19.2 to 26.4 V, rated power 1.5 VA, resistance 190 Ω, consumption 53 mA, holding voltage 19.2 V, must drop-out voltage 4.8 V, option: Lockable test button + mechanical indicator, ambient temperature from -40 to +85 °C

BROWSE PRODUCT PAGE

Technical Features:

Ambient temperature range:	-40...85 °C
Commercial Description:	General purpose plug-in relay. 4 CO 7 A. For use with 94 Series sockets. AC or DC coil. Lockable test button option and mechanical indicator as standard Variant with LED and integrated protection circuit.
Contact configuration:	4 pole, CO (nPDT)
Dimensions:	20.7x37.2x27.7 mm
Electrical life:	150000 cycles
Insulation coil/contacts:	4 kV
Nominal voltage AC:	24 V
Operating range AC:	19.2...26.4 V
Rated contact voltage:	250 V AC
Rated current (contacts):	7
Rated power AC:	1.5 VA
Supply:	AC coil
Certifications and quality approvals (according to type):	

The information, technical details, data and features contained in this document are subject to change or modification at any time.
It is for information purposes only and does not form
the basis of a contract.

Need more information?
Contact our sales Find a dealer

Finder 2026 - All rights reserved
Findernet.com
Technical Information