810102300000

Modular timer 16 A



This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

Technical description:
Modular timers, Multi-function, 1 CO (SPDT), 16 A, AC/DC coil, 230 V, operating from 10.8 to 250 V (AC)/(DC), rated power 2 VA (AC)/(DC), ambient temperature from -10 to +50 °C

BROWSE PRODUCT PAGE

Technical Features:

Commercial Description:	Modular timer, Multi-voltage (non polarized DC), Multi-function, suitable for 35mm rail (EN60715) mount.
Contact configuration:	1 CO (SPDT)
Delay setting:	(0.1...1)s, (1...10)s, (10...60)s, (1...10)min, (10...60)min, (1...10)h
Dimensions:	17.5x84x56.5 mm
Functions:	Multi-function
Nominal voltage:	230 V
Operating range AC:	10.8...250 V
Operating range DC:	10.8...250 V
Rated contact voltage:	250 V AC
Rated current (contacts):	16 A
Certifications and quality approvals (according to type):	

The information, technical details, data and features contained in this document are subject to change or modification at any time.
It is for information purposes only and does not form
the basis of a contract.

Need more information?
Contact our sales Find a dealer

Finder 2025 - All rights reserved
Findernet.com
Technical Information