223200244340

Modular contactor



This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

Technical description:
Modular contactor, 25 A, 2 pole, NO, 25 A, AgSnO2, AC/DC coil, 24 V, operating from 19.2 to 26.4 V (AC)/(DC), rated power 2 VA (AC) / 2.2 W (DC), holding voltage 9.6 V (AC)/(DC), must drop-out voltage 2.4 V (AC)/(DC), option: Auto-On-Off selector + mechanical indicator + LED, ambient temperature from -25 to +50 °C

BROWSE PRODUCT PAGE

Technical Features:

Ambient temperature range:	-25...50 °C
Commercial Description:	Modular contactor 25 A, 2 contacts, 17.5mm width, NO contact gap ≥ 3 mm, double break. Suitable for railway applications; plastic materials compliant with fire and smoke regulations (EN 45545-2 + A1: 2016).
Contact configuration:	2 pole, NO
Dimensions:	17.5x84x56.5 mm
Electrical life:	30000 cycles
Insulation coil/contacts:	6 kV
Nominal voltage:	24 V
Operating range AC:	19.2...26.4 V
Operating range DC:	19.2...26.4 V
Rated contact voltage:	250 V AC
Rated current (contacts):	25
Supply:	AC/DC
Certifications and quality approvals (according to type):	

The information, technical details, data and features contained in this document are subject to change or modification at any time.
It is for information purposes only and does not form
the basis of a contract.

Need more information?
Contact our sales Find a dealer

Finder 2026 - All rights reserved
Findernet.com
Technical Information

All the data displayed in this file are automatically generated by our online catalogue.
Complete data can be found in the user documentation.
Creation Date 31/08/2026.