773182308050

Solid State Relays 5 - 15 - 30 - 50 A



This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

Technical description:
Solid State Relays, 30 A Output, 1 pole, modular housing, Output circuit 230 V AC, Input and output terminals on opposite sides, Switch-on mode: Zero-crossing, AC supply version, nominal voltage 230 V, operating from 40 to 280 V, rated power 7.5 VA (AC) / 0.9 W (DC), consumption 25 mA, must drop-out voltage 6 V, ambient temperature from -20 to +80 °C

BROWSE PRODUCT PAGE

Technical Features:

Ambient temperature range:	-20...80 °C
Commercial Description:	Modular solid state relay, 1 NO 30A output with 22.5 width, heat sink + plastic casing. The Type 77.31 features a 60 to 440V AC output (with dual SCR) and high switching speed and electrical life. Versions available with “Zero-crossing” or “Random” switch-on.
Contact configuration:	1 NO
Dimensions:	22.5x104.5x116.3 mm
Electrical life:	10000000 cycles
Nominal voltage AC:	230 V
Operating range AC:	40...280 V
Rated contact voltage:	400 V AC
Rated current (contacts):	30 A
Rated power AC:	7.5 VA
Rated power DC:	0.9 W
Supply:	AC supply version
Certifications and quality approvals (according to type):	

The information, technical details, data and features contained in this document are subject to change or modification at any time.
It is for information purposes only and does not form
the basis of a contract.

Need more information?
Contact our sales Find a dealer

Finder 2025 - All rights reserved
Findernet.com
Technical Information