703184002022

Monitoring relays



This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

Technical description:
Electronic voltage monitoring relays, 3 phase AC line monitoring, 1 pole, 6 A, AC supply version, nominal voltage 400 V, operating from 220 to 510 V, rated power 11 VA, Detection values: 2 adjustable detection values, CO (nPDT), Time delay setting: Adjustable switch-off delay, Fault memory option: Fault memory function selectable, ambient temperature from -20 to +60 °C

BROWSE PRODUCT PAGE

Technical Features:

Ambient temperature range:	-20...60 °C
Commercial Description:	Line voltage monitoring relay for three-phase networks. Multi-function model for monitoring three-phase (380 ... 415)V undervoltage, overvoltage, window mode (overvoltage + under-voltage), phase rotation and phase loss (detects phase loss error even in the presence of regenerated voltages) Voltage fault memory – selectable.
Contact configuration:	1 pole, CO (nPDT)
Dimensions:	35x84x56.5 mm
Nominal voltage:	380...415 V
Operating range AC:	220...510 V
Rated contact voltage:	250 V AC
Rated current (contacts):	6
Supply:	AC supply version
Certifications and quality approvals (according to type):	

The information, technical details, data and features contained in this document are subject to change or modification at any time.
It is for information purposes only and does not form
the basis of a contract.

Need more information?
Contact our sales Find a dealer

Finder 2026 - All rights reserved
Findernet.com
Technical Information

All the data displayed in this file are automatically generated by our online catalogue.
Complete data can be found in the user documentation.
Creation Date 31/08/2026.