



ZK 235-11Z-M20

- Snap action with constant contact pressure up to switching point
- 1 Cable entry M 20 x 1.5
- Metal enclosure
- Wide range of alternative actuators
- Good resistance to oil and petroleum spirit
- 30 mm x 63,5 mm x 30 mm
- Actuator heads can be repositioned by 4 x 90°
- Mounting details to EN 50047

Data

Ordering code

Note (Delivery capacity)	Not available!
Product type description	ZK 235-11Z-M20
Article number (order number)	101164307
EAN (European Article Number)	4030661205458
eCl@ss number, version 12.0	27-27-26-01
eCl@ss number, version 11.0	27-27-26-01
eCl@ss number, version 9.0	27-27-26-01
ETIM number, version 7.0	EC000030
ETIM number, version 6.0	EC000030

Approvals - Standards

Certificates	cULus
	CCC

General data

Standards	BG-GS-ET-15
	EN IEC 60947-5-1
	EN ISO 13849-1
Housing construction form	Norm construction design

General data

Actuator type to EN 50047	E
Housing material	Metal, zinc die-cast
Gross weight	155 g

General data - Features

Safety functions	Yes
Number of auxiliary contacts	1
Number of safety contacts	1

Safety classification

Standards	EN IEC 60947-5-1
Mission time	20 Year(s)

Safety classification - Safety outputs

B10D Normally-closed contact (NC)	20,000,000 Operations
-----------------------------------	-----------------------

Mechanical data

Actuating element	Offset roller lever
Mechanical lifetime, minimum	20,000,000 Operations
Actuating force, minimum	9 N
Positive break force, minimum	19 N
Actuating speed, minimum	24 mm/min
Actuating speed, maximum	1 m/s
Note (Actuating speed)	Actuating speed with actuating angle 30° to switch axis

Mechanical data - Connection technique

Termination	Screw terminals M20 x 1.5
Cable section, minimum	0.75 mm ²
Cable section, maximum	2.5 mm ²
Note	All indications including the conductor ferrules.

Mechanical data - Dimensions

Length of sensor	30 mm
Width of sensor	30 mm

Mechanical data - Dimensions

Height of sensor	95.1 mm
------------------	---------

Ambient conditions

IP Degree of protection	IP67
	IP65
Ambient temperature	-30 ... +80 °C

Ambient conditions - Insulation values

Rated insulation voltage Ui	500 V
Rated impulse withstand voltage Uimp	6 kV

Electrical data

Thermal test current	10 A
Required rated short-circuit current	1,000 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	1 A
Switching element	1 NO contact, 1 NC contacts
Switching principle	Snap action
Bounce duration, maximum	3 ms
Maximum switching frequency	5,000 /h
Switchover time, minimum	5.5 ms
Material of the contacts, electrical	Silver

Pictures

Product picture (catalogue individual photo)




ID: k235kf01

[| 691.92 KB | .jpg | 1000 x 2125 Pixel](#)

[| 25.86 KB | .jpg | 165 x 350 Pixel](#)


[| 91.19 KB | .png | 210 x 446 Pixel](#)

Dimensional drawing basic component




ID: 1-235g01
| 114.75 KB | .jpg | 1000 x 831 Pixel
| 4.03 KB | .png | 210 x 174 Pixel

Dimensional drawing actuator



ID: 1k236g01
| 67.42 KB | .jpg | 1000 x 697 Pixel
| 3.64 KB | .png | 210 x 146 Pixel

Switch travel diagram



ID: kk235s18
| 70.44 KB | .jpg | 1000 x 539 Pixel
| 2.47 KB | .png | 210 x 113 Pixel

Diagram



ID: k1o1sk01
| 52.24 KB | .jpg | 1000 x 407 Pixel
| 2.58 KB | .png | 210 x 85 Pixel

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on: 31/08/2026, 14:06