



ZV7H 235-11Z-M20

- Snap action with constant contact pressure up to switching point
- 1 Cable entry M 20 x 1.5
- Metal enclosure
- Wide range of alternative actuators
- Good resistance to oil and petroleum spirit
- 30 mm x 63,5 mm x 30 mm
- Actuator heads can be repositioned by 4 x 90°
- Mounting details to EN 50047
- only for positioning tasks
- Lever angle adjustable in 10° steps

Data

Ordering code

Product type description	ZV7H 235-11Z-M20
Article number (order number)	101168066
EAN (European Article Number)	4030661220437
eCl@ss number, version 12.0	27-27-26-01
eCl@ss number, version 11.0	27-27-26-01
eCl@ss number, version 9.0	27-27-26-01
ETIM number, version 7.0	EC000030
ETIM number, version 6.0	EC000030

Approvals - Standards

Certificates	cULus
	CCC

General data

Standards	BG-GS-ET-15
	EN IEC 60947-5-1
	EN ISO 13849-1
Housing construction form	Norm construction design

General data

Housing material	Metal, zinc die-cast
Lever material	Metal film
Gross weight	225 g

General data - Features

Number of auxiliary contacts	1
Number of safety contacts	1

Safety classification

Standards	EN ISO 13849-1
Mission time	20 Year(s)

Mechanical data

Actuating element	Roller lever
Roller material	Plastic
Mechanical lifetime, minimum	20,000,000 Operations
Actuating speed, minimum	240 mm/min
Actuating speed, maximum	1 m/s
Note (Actuating speed)	Actuating speed with actuating angle 30° to switch axis
Actuating torque, minimum	0.2 Nm

Mechanical data - Connection technique

Termination	Screw terminals M20 x 1.5
Cable section, minimum	0.75 mm ²
Cable section, maximum	2.5 mm ²
Note	All indications including the conductor ferrules.
Wire cross-section	13 AWG

Mechanical data - Dimensions

Length of sensor	49 mm
Width of sensor	30 mm
Height of sensor	160.5 mm

Ambient conditions

IP Degree of protection	IP67
	IP65
Ambient temperature	-30 ... +80 °C

Ambient conditions - Insulation values

Rated insulation voltage U_i	500 V
Rated impulse withstand voltage U_{imp}	6 kV

Electrical data

Thermal test current	10 A
Required rated short-circuit current	1,000 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	1 A
Switching element	1 NO contact, 1 NC contacts
Switching principle	Snap action
Bounce duration, maximum	3 ms
Maximum switching frequency	5,000 /h
Switchover time, maximum	5.5 ms
Material of the contacts, electrical	Silver

Pictures


Product picture (catalogue individual photo)



ID: k235hf02


| 1.79 MB | .jpg | 1000 x 3829 Pixel
| 30.25 KB | .jpg | 91 x 350 Pixel
| 334.02 KB | .png | 210 x 804 Pixel

Dimensional drawing basic component




ID: 1-235g01
[| 114.75 KB | .jpg | 1000 x 831 Pixel](#)
[| 4.03 KB | .png | 210 x 174 Pixel](#)

Dimensional drawing actuator



ID: 1h236g06
[| 102.24 KB | .jpg | 1000 x 693 Pixel](#)
[| 9.66 KB | .png | 210 x 145 Pixel](#)

Switch travel diagram



ID: kh235s14
[| 82.21 KB | .jpg | 1000 x 544 Pixel](#)
[| 2.45 KB | .png | 210 x 114 Pixel](#)

Diagram



ID: k1o1sk01
[| 52.24 KB | .jpg | 1000 x 407 Pixel](#)
[| 2.58 KB | .png | 210 x 85 Pixel](#)

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on: 31/08/2026, 14:18