



ZS 335-11Z-M20

- Snap action with constant contact pressure up to switching point
- 1 Cable entry M 20 x 1.5
- Metal enclosure
- Wide range of alternative actuators
- Good resistance to oil and petroleum spirit
- 40,5 mm x 76 mm x 38 mm
- Actuator heads can be repositioned by 4 x 90°
- Design to EN 50041

Data

Ordering code

Note (Delivery capacity)	Not available!
Product type description	ZS 335-11Z-M20
Article number (order number)	101166484
EAN (European Article Number)	4030661215358
eCl@ss number, version 12.0	27-27-26-01
eCl@ss number, version 11.0	27-27-26-01
eCl@ss number, version 9.0	27-27-26-01
ETIM number, version 7.0	EC000030
ETIM number, version 6.0	EC000030

Approvals - Standards

Certificates	cULus
	CCC

General data

Housing construction form	Norm construction design
Actuator type to EN 50041	B
Housing material	Light alloy die-casting
Housing coating material	painted

General data

Gross weight	185 g
--------------	-------

General data - Features

Safety functions	Yes
Number of auxiliary contacts	1
Number of safety contacts	1

Safety classification

Standards	EN IEC 60947-5-1
Mission time	20 Year(s)

Safety classification - Safety outputs

B10D Normally-closed contact (NC)	20,000,000 Operations
-----------------------------------	-----------------------

Mechanical data

Actuating element	Plunger
Mechanical lifetime, minimum	30,000,000 Operations
Actuating force, minimum	12 N
Actuating speed, maximum	0.5 m/s
Note Bounce duration	Bounce duration in accordance with actuating speed

Mechanical data - Connection technique

Termination	Screw terminals M20 x 1.5
Cable section, minimum	0.75 mm ²
Cable section, maximum	2.5 mm ²
Note	All indications including the conductor ferrules.

Mechanical data - Dimensions

Length of sensor	38 mm
Width of sensor	40.5 mm
Height of sensor	103.5 mm

Ambient conditions

IP Degree of protection	IP67
	IP65

Ambient conditions

Ambient temperature	-30 ... +80 °C
---------------------	----------------

Ambient conditions - Insulation values

Rated insulation voltage U_i	500 V
Rated impulse withstand voltage U_{imp}	6 kV

Electrical data

Thermal test current	10 A
Required rated short-circuit current	1,000 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	4 A
Switching element	1 NO contact, 1 NC contacts
Switching principle	Snap action
Maximum switching frequency	5,000 /h
Switchover time, maximum	2 ms
Material of the contacts, electrical	Silver

Pictures

Product picture (catalogue individual photo)




ID: k335sf01

[| 918.41 KB | .jpg | 1000 x 2152 Pixel](#)

[| 28.37 KB | .jpg | 163 x 350 Pixel](#)

[| 109.61 KB | .png | 210 x 452 Pixel](#)

Dimensional drawing basic component




ID: 1-335g01

[| 105.79 KB | .jpg | 1000 x 697 Pixel](#)

[| 4.51 KB | .png | 210 x 146 Pixel](#)

Dimensional drawing actuator




ID: 1s336g01

| 52.58 KB | .jpg | 1000 x 703 Pixel

| 2.74 KB | .png | 210 x 148 Pixel

Switch travel diagram



ID: kr335s12

| 66.97 KB | .jpg | 1000 x 533 Pixel

| 2.36 KB | .png | 210 x 112 Pixel

Diagram



ID: k1o1sk01

| 52.24 KB | .jpg | 1000 x 407 Pixel

| 2.58 KB | .png | 210 x 85 Pixel

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on: 31/08/2026, 14:22