
K50 SERIE



Crimping dies R 50, indent crimping



Suitable for

- Tubular cable lugs and connectors - Cu, standard type

Cross section mm²	For item	Part No.
0.75 - 2.5	91R, 92R, 93R	**R501**
4 - 10	94R, 95R, 2R	**R502**

Crimping dies D 50

NEW



Suitable for

- Compression cable lugs to DIN 46235 and connectors to DIN 46267, part 1 - Cu

Cross section mm²	Part No.
6 - 16	**D504**
16 - 25	**D505**

Crimping dies R 50, hexagonal crimping

NEW




Suitable for

- Tubular cable lugs and connectors - Cu, standard type

Cross section mm²	Part No.
6 - 16	**R504**
16 - 25	**R505**

Crimping dies Q 50




Suitable for

- Solderless terminals to DIN 46234 and pin terminals to DIN 46230 - Cu
- Solderless connectors to DIN 46341 - Cu

Cross section mm²	Part No.
0.5 - 10	**Q501**

Crimping dies M 50




Suitable for

- Tubular cable lugs and connectors for solid conductors

Cross section mm²	Part No.
1.5 - 4	**M50154**
6 - 10	**M50610**

Crimping dies AE 50



Suitable for

- Cable end-sleeves

Cross section mm²	Part No.
0.14 - 10	**AE501**
10 - 25	**AE502**
35 - 50	**AE503**

Crimping dies IS 50, single crimping




Suitable for

- Insulated cable connections, single crimping

Cross section mm²	Part No.	for item
10 - 16	**IS5072**	ST1716IS, ST1717IS, 652C5, 652C6, 653C6
0.5 - 2.5	**IS504**	670 WS, 680 WS
4 - 6	**IS505**	700 WS

Crimping dies IS 50, double crimping




Suitable for

- Insulated cable connections, double crimping

Cross section mm²	Part No.	for item
0.5 - 6	**IS501**	
0.1 - 1	**IS503**	8201-8201B

Crimping dies CR 50




Suitable for

- Non-insulated receptacles

Cross section mm²	Part No.	for item	Tab Width
0.25 - 6	**CR501**		2.8 / 6.3
0.5 - 2.5	**CR502**		4.8
0.5 - 1	**CR503**	38201, 38201A	2.8
0.5 - 2.5	**CR504**	3720, 3735	6.3
0.5 - 1.5	**CR505**	3725	6.3

Crimping dies BNC 50



Suitable for

- Stud and shielded sleeves
- BNC plugs for coax cable RG 58, 59, 62 and 71

Part No.
BNC501

Crimping dies SB 50



Suitable for

- Turned pin receptacles
- Pin connectors

Cross section mm²	Part No.
0.1 - 1; 1.5 - 2.5; 4	**SB501**