EKM 60 UNV Battery-powered hydraulic universal tool 6 - 300 mm²

NEXT GENERATION



- One head for crimping, cutting and punching - one tool for all
- Ideal in the assembly field where all common jobs can be carried out using one tool
- All tool data on view thanks to display and i-press app
- Small and slim, perfect for cramped conditions

Characteristics

- Choose your battery system: Bosch or Makita
- All data can be easily read via Bluetooth
- Universal head flip top style, rotatable
- Simple and safe: One-button operating concept for controlling all tool functions
- Effortless working due to balanced centre of gravity
- LED for work area illumination
- Simple and safe: Automatic retraction when operation is complete (crimping or cutting)
- Always ready-to-use thanks to battery charge and service display

Technical instructions

- Interchangeable adapters and dies for crimping, cutting and punching you will find on page 470

IEC

K22 SERIE | K18 SERIE | K5 SERIE

Technical data	
Crimping force	60 kN
Stroke	42 mm
Crimping range	6 - 300 mm²
Crimping cycle	7 s up to 9 s (depending on cross-section)
Cutting range	max. 40 mm dia.
Punching capacity	up to 64 mm dia. round, up to 92 x 92 mm square
Charging time	15 min.
Weight	3.0 kg
Ambient temperature	-10 °C up to +40 °C

Item	Part No. **Bosch**	Part No. **Makita**	
Battery-powered hydraulic universal tool 6 - 300 mm²	**EKM60UNVCFB**	**EKM60UNVCFM**	
Scope of supply			Page
Bosch battery 18 V / 2.0 Ah, Li-Ion	RALB1EU		484
Bosch quick-charger for 18 V Li-Ion battery	LGLB1EU		486
Makita battery 18 V / 1.5 Ah, Li-Ion		RAL1	483
Makita quick-charger for 18 V Li-Ion battery		LGL1	486
Adapter for crimping dies of Series 22	UA22	UA22	470
Plastic case 450 x 370 x 105 mm	KKMUNVNG	KKMUNVNG	
Accessories			Page
Bosch battery 18 V / 5.0 Ah, Li-Ion	RALB2EU		485
Makita battery 18 V / 3.0 Ah, Li-Ion (54 Wh)		RAL2	483
Variants			Page
L-BOXX with battery powered universal tool EKM60UNVCFB	LBOXXEKM60UNVCFB		203
L-BOXX with battery powered universal tool EKM60UNVCFM		LBOXXEKM60UNVCFM	203