IKFSI5 21.01.2014



General Data

Type Reference	IKFSI5
Description	Fuse terminal
Approvals	CE, UKCA
Terminal type	Fuse terminal for automotive fuse-links
Terminal width	8.1 mm
Mounting method	top hat rail N35, EN60715 TH35
Connection type	screw connection, slotted screw
Thread size of screw connection	M3
Torque	0.8 Nm
Rated cross section	4 mm²
Wire size (solid)	0.5 ... 6 mm²
Wire size (stranded)	0.5 ... 4 mm²
Rated current	20 A max.
Max. storage temperature	-40°C ... 80°C
Max. operating temperature	-30°C ... 40°C
Photo	

Data acc. to IEC 60947-7-1

Flammability class acc. to UL94	V2
Pollution degree	3
Overvoltage category	III
Material group	II
Insulating material	PA 6.6
Stripping length	7 mm
Rated insulation voltage	250 V

Note

- max. power dissipation at compound arrangement: 3 W

It is the responsibility of each user to use the appropriate fuses. (max. terminal temperature 90°C)

Georg Schlegel GmbH & Co. KG
Kapellenweg 4
88525 Dürmentingen / Germany

+49 (0)7371 / 502-0
+49 (0)7371 / 502 49
@ info@schlegel.biz
www.schlegel.biz



Georg Schlegel GmbH & Co. KG
Kapellenweg 4
88525 Dürmentingen / Germany
+49 (0)7371 / 502-0
+49 (0)7371 / 502 49
@ info@schlegel.biz
www.schlegel.biz