Cables 300/300 V

PLANAFLEX H03VVH2-F





Description

PLANAFLEX H03VVH2-F cables are indicated for indoor mobile installations and household appliances with medium mechanical strain, being mainly used for domestic applications.

Reference Standards: UNE-EN 50525-2-11, EN 50525-2-11

Dimensions

Section (mm^2)	Resistance at 20 °C (Ohm/km)	External Diameter (mm)	Weight (kg/km)	Class
2x0,5	39	3,20 x 5,30	29	Eca
2x0,75	26	3,40 x 5,60	34	Eca

Applications

Suitable for the following installations:
- Indoor or receiver installations
- Installations in premises with special characteristics
- Receiver installations
- Electrical installations in furnishings

Technical Characteristics

1 Conductor	Class V Electrolyte copper in accordance with UNE-EN 60228, EN 60228
2 Insulation	PVC insulation, type TI-2, according to BS7655, UNE-EN 50363-3 and EN 50363-3
3 Sheath	PVC sheath, Type TM-2, according to BS 7655, UNE-EN 50363-4-1 and EN 50363-4-1
4 Nominal voltage	300/300 V
5 Test voltage	2.000 V C.A.
6 Maximum temperature	70 ºC
7 Other characteristics	

Colour according UNE 21089 and HD 308S2
Non flame propagating according to UNE-EN 60332-1-2, EN 60332-1-2 and IEC 60332-1-2
CPR classification according to EN 50575

The information contained on this page is for information only and does not constitute a contractual commitment of any kind from Cables RCT. 15 January 2021
Cables RCT, as a consequence of his continuous improvement process, may modify any technical specification without further notice.

cablesrct.com

HEADQUARTER ZARAGOZA
T. 976 500 120
info@rct.es

DELEGATION BARCELONA
T. 93 307 95 62
barna@rct.es

DELEGATION MADRID
T. 91 691 85 48
madrid@rct.es

DELEGATION SEVILLA
T. 954 354 946
sevilla@rct.es

DELEGATION VALENCIA
T. 96 375 90 70
valencia@rct.es