
Date: 15.09.2026

# Installation trunking LFG 15x30-9010, PVC, with base perforation, pure white



## Product description

PVC installation trunking according to DIN EN 50085-2-1 for cable laying on walls and ceilings, consisting of a completely overlapping cover and base with single-row base perforation for fastening.
**Note:** Sound and fire protection measures must be carried out professionally.

## Basic data

| | |
|---|---|
| Item number | 11026 |
| Product group | 10-Cable routing |
| Packing unit | 72 meters |
| EAN code | 4018475253933 |
| Tariff number | 39259020 |

## Technical features

| | |
|---|---|
| Height | 16 mm |
| Width | 30 mm |
| Length | 2000 mm |
| Useful cross section | 340 mm² |
| Material | plastic |
| Halogen free | no |
| Anti-bacterial treatment | no |
| Surface protection | other |
| Suitable for circuit integrity | no |
| Colour | white |
| Transparent | no |
| RAL-number | 9010 |
| Number of permanent partitions | 0 |
| Number of plug-in partitions | 0 |
| Type of fastening | Bottom perforation |
| Cover model | loose |
| With cable fixing clip | no |
| With protective foil | no |
| With duct connector | no |
| Delivery on roll | no |
| Pre-stamping | no |
| Degree of protection (IP) | IP30 |
| Impact strength | IK08 |
| Operating temperature | from -5 to 60 °C |