The basic hanging cabinets for indoor use. Thanks to the welded structure, the cabinets are safe even with maximum loads. Two-piece structure allows an easy access from the rear to the installed devices. At the bottom and on the top of the cabinets there are holes (250 x 70mm) for cable bundles. The rear part that is mounted to the wall has also two holes for cable bundles (at the top and bottom). Additionally, there are two holes on the top and two holes at the bottom for ventilation units.



Basic parameters:
- Material: steel sheet
- Front door: sheet metal/glass
- Back door: rear metal pivoting wall
- Load: 30-50 kg
- IP Rating: 20
- Colour: RAL 7035

Delivery includes:
- 1 brush strip
- set of M6 assembly bolts (16 pcs)
- 2 front door keys

Maximum spacing of mounting sections depending on cabinet depth:
- cabinets 500 mm in depth - maximum spacing 435 mm
- cabinets 600 mm in depth - maximum spacing 535 mm

Compliance with:
EIA-310-D, IEC 60297-1, IEC 60297-2, ROHS



Available dimensions:

Type	Width (mm)	Depth (mm)	Height (mm)	Weight (kg)	Load capacity (kg)	Index
6U	600	500	330	19,1	40	11042501.1V
9U	600	500	465	22,1	40	11043501.1V
12U	600	500	600	25,9	40	11045501.1V
15U	600	500	730	29,7	50	11046501.1V
18U	600	500	860	33,5	50	11047501.1V
21U	600	500	997	37,4	50	11049501.1V
4U	600	600	240	16,1	30	11041601.1V
6U	600	600	330	19,5	40	11042601.1V
9U	600	600	465	22,5	40	11043601.1V
12U	600	600	600	26,3	40	11045601.1V
15U	600	600	730	30,1	50	11046601.1V
18U	600	600	860	33,9	50	11047601.1V
21U	600	600	997	37,8	50	11049601.1V