Data sheet

Part No.	**FXKVM SW**
Description	slip type coupler
Properties	for sandtight connections of FXKVR and FXKVS ductings
Colour	black, similar to RAL 9005
Classification	N 450, IP40



Standard: EN 61386-1, EN 61386-24, EN 50626-1, EN 50626-2, OVE E 8635

Working temperature
-30 to +70 °C

Art. No.	ED	ID	PU	PU
055202	42,9 mm	40 mm	1 pc	-
025755	57,9 mm	50 mm	1 pc	200 pc
025756	73 mm	63 mm	1 pc	60 pc
025757	84,2 mm	75 mm	1 pc	37 pc
025758	100,5 mm	90 mm	1 pc	60 pc
025102	129 mm	110 mm	1 pc	12 pc
032331	142,2 mm	125 mm	1 pc	32 pc
025759	173,9 mm	160 mm	1 pc	8 pc
041351	193 mm	175 mm	1 pc	-
040801	221 mm	200 mm	1 pc	10 pc

Further technical details

Details	
With rubber seal	false
Surface protection	Untreated
Surface polished	false
Halogen free	true
Material	PE

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt´s belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, office@dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.