Data sheet

Part No.	**HFSB LG**
Description	normal bend, halogen-free
Properties	for the connection of rigid conduits in an angle of 90°, especially for enclosed installations dimensions 16 to 25 with moulded-on coupler, dimensions 32 and above with intented coupler
Colour	light grey, similar to RAL 7035
Fire Behaviour	non flame propagating



Standard: EN 61386-1, EN 61386-21, EN 60754, EN 50642, EN 61034, IEC 63355



HFT LSF0H halogenfrei HFT LSF0H HFT LSF0H LSF0H

Working temperature
-25 to +105 °C

Art. No.	For tube diameter	Radius	PU	PU
106158	16 mm	50 mm	50 pc	600 pc
106159	20 mm	70 mm	25 pc	300 pc
106160	25 mm	95 mm	25 pc	200 pc
106161	32 mm	125 mm	15 pc	120 pc
106162	40 mm	160 mm	50 pc	1750 pc
106163	50 mm	210 mm	40 pc	960 pc
106164	63 mm	270 mm	20 pc	480 pc

Further technical details

Details	
Model	Plug-in
With inspection opening and cover	false
Angle	90 °
Material	PP-Blend

Cardboard packaging used is made from 100% waste paper and is fully recyclable,
plastic packaging is fully recyclable.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt´s belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, office@dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.