

# H-2(Z) - Thin-wall heat shrink tubing

## H-2(Z) - Thin-wall heat shrink tubing - 2:1 - Operating temperature up to 125 °C



### Technical specifications

Brand	: WKK (produced by Hongshang)
Shrink ratio	: 2:1
Flame retardant	: Yes
Self-extinguishing	: Yes
Adhesive	: No
Operating temperature	: -55 °C up to +125 °C
Minimum shrink temperature	: +70 °C
Minimum full recovery temperature	: +110 °C
Longitudinal change	: 0 up to 10% max.
Material	: Crosslinked polyolefin
Halogen-free	: No
Approvals	: UL E204071, CSA, RoHS
Available colors	: Black (UV resistant)= ● White= ○ Red= ● Blue= ● Yellow= ● Green= ● Purple= ● Brown= ● Orange= ● Grey= ●

Scan this QR code for article numbers, current prices and stock information and to order directly.

Type / Size	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Packaging type			
				Reel (meter)	Minibox (meter)	Length piece (mm)	
H-2(Z) 1.2/0.6	1.2	0.6	0.33	150	10	1.000	1.220
H-2(Z) 1.6/0.8	1.6	0.8	0.36	150	10	1.000	1.220
H-2(Z) 2.4/1.2	2.4	1.2	0.42	150	10	1.000	1.220
H-2(Z) 3.2/1.6	3.2	1.6	0.42	150	10	1.000	1.220
H-2(Z) 4.8/2.4	4.8	2.4	0.52	75	10	1.000	1.220
H-2(Z) 6.4/3.2	6.4	3.2	0.52	75	5	1.000	1.220
H-2(Z) 9.5/4.8	9.5	4.8	0.52	75	5	1.000	1.220
H-2(Z) 12.7/6.4	12.7	6.4	0.62	50	5	1.000	1.220
H-2(Z) 16.0/8.0	16.0	8.0	0.67	50	5	1.000	1.220
H-2(Z) 19.0/9.5	19.0	9.5	0.75	30	5	1.000	1.220
H-2(Z) 25.4/12.7	25.4	12.7	0.85	30	5	1.000	1.220
H-2(Z) 32.0/16.0	32.0	16.0	0.85	30	-	1.000	1.220
H-2(Z) 38.1/19.0	38.1	19.0	0.96	30	-	1.000	1.220
H-2(Z) 50.8/25.4	50.8	25.4	0.97	30	-	1.000	1.220
H-2(Z) 76.2/38.1	76.2	38.1	1.17	15	-	1.000	1.220
H-2(Z) 102.0/50.8	102.0	50.8	1.30	15	-	-	-
H-2(Z) 126.0/63.5	126.0	63.5	1.30	15	-	-	-
H-2(Z) 150.0/76.0	150.0	76.0	1.30	15	-	-	-