Heat shrink butt connectors - Insulated



Scan this QR code for article numbers, current prices and stock information and to order directly.

Technical specifications

Brand	: WKK
Crimp terminal type	: Heat shrink butt connectors
Temperature range	: 600 V max.
Operating temperature (°C)	: -55 °C up to +125 °C
Min. shrink temperature (°C)	: 180 °C
Insulation material	: Nylon (PA66)
Connector material	: Tin plated copper
Approvals	: RoHS

Type no.	Color	Wire range (mm²)	AWG	Overall length (mm)	PU (pcs.)
Ver 0.5 t heat shrink	Transparent	0.25 ~ 0.5	26 ~ 24	28	100
Ver 1.25 r heat shrink	Red	0.5 ~ 1.5	22 ~ 18	35	100
Ver 2 b heat shrink	Blue	1.5 ~ 2.5	16 ~ 14	35	100
Ver 5.5 g heat shrink	Yellow	4.0 ~ 6.0	12 ~ 10	41	100

Heat shrink solder butt connectors - Insulated



Scan this QR code for article numbers, current prices and stock information and to order directly.

Technical specifications

Brand	: WKK
Crimp terminal type	: Heat shrink solder butt connectors
Operating temperature (°C)	: -55 °C up to +125 °C
Shrink temperature (°C)	: > +140 °C
Insulation material	: Polyolefin

Type no.	Color	Wire range (mm²)	Overall Length (mm)	PU (pcs.)
Solder 0.3 - 0.8 transp.	Transparent	0.3 ~ 0.8	26	100
Solder 0.8 - 2.0 red	Red	0.8 ~ 2.0	42	100
Solder 2.0 - 4.0 blue	Blue	2.0 ~ 4.0	42	100
Solder 4.0 - 6.0 yellow	Yellow	4.0 ~ 6.0	42	100