Data sheet

Part No.	**KM BK UV**
Description	grip type coupler, chlorine-free for waterproof and tight connection of pliable conduits especially for use in concrete installation, protection type IP65, extraction resistance 250 N
Colour	black, similar to RAL 9005
Fire Behaviour	non flame propagating
Classification	IP 65





Standard: EN 61386-1, EN 61386-22

Working temperature	UV resistant
-25 to +90 °C	true – up to 10 years

Art. No.	For tube diameter	PU	PU
085726	16 mm	100 pc	1200 pc
084051	20 mm	100 pc	800 pc
084052	25 mm	50 pc	600 pc
085926	32 mm	25 pc	300 pc
102335	40 mm	25 pc	200 pc
102336	50 mm	15 pc	120 pc
102337	63 mm	8 pc	64 pc

Further technical details

Details	
Halogen free	False
Model	Extraction proof
Material	PE

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt´s belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.

11.09.2024