Data sheet

Part No.	**SALR GR**
Description	rigid aluminium conduit (Al Mg Si 0.5-F22), without thread heavy compression resistance, heavy impact resistance, lead-free
Fire Behaviour	non flame propagating
Classification	44561
Compression resistance	> 1250 N





Standard: EN 61386-1, EN 61386-21

Compressive strength class	Impact strength	Working temperature	UV stabilized
Heavy (class 4)	Heavy (class 4)	-45 to +250 °C	true – up to 10 years

Art. No.	ED	ID	PU	PU
035458	16 mm	14,2 mm	3 m	15 m
035250	20 mm	18,2 mm	3 m	15 m
035251	25 mm	23 mm	3 m	15 m
035252	32 mm	29,8 mm	3 m	15 m
035253	40 mm	37,6 mm	3 m	15 m
035254	50 mm	47,6 mm	3 m	15 m
035255	63 mm	60,4 mm	3 m	15 m

Areas of Recommended Application

Area	
Flush mounted (plaster)	False
Surface mounted	True
Suitable for concrete installation	False
Machine and systems installation	True
Suitable for subsurface installation (screed)	False
Outdoor installation	True
Installation on wood	True
Suitable for hollow wall installation	True
Installation in underground	False

Further technical details

Details	
Model	Rigid non-threaded
Surface protection	Untreated
Material quality	Other
Material	Aluminium

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt´s belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, office@dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.