Data sheet

Part No.	**SGL GR**
Description	straight gland
	for corrugated conduits, with patented plug-in system for quick-fit assembly, pull-tight connection, with metric thread according to EN 60423
Colour	grey, similar to RAL 7001
Fire Behaviour	non flame propagating
Classification	IP54



Standard: EN 61386-1, EN 61386-23, EN 60754



Working temperature	Degree of protection (IP)
-25 to +105 °C	IP54

Art. No.	Nominal diameter	Thread	Thread length	Total length	PU	PU
016440	12 mm	M12 x 1.5	8 mm	18,3 mm	100 pc	3200 pc
012699	16 mm	M16 x 1.5	10,5 mm	18,9 mm	100 pc	1600 pc
012700	20 mm	M20 x 1.5	12 mm	24 mm	50 pc	1200 pc
012701	25 mm	M25 x 1.5	15 mm	30,4 mm	50 pc	600 pc
012702	32 mm	M32 x 1.5	15 mm	32 mm	30 pc	360 pc
015509	40 mm	M40 x 1.5	15 mm	38 mm	20 pc	240 pc
015508	50 mm	M50 x 1.5	15 mm	42,4 mm	16 pc	128 pc
043075	63 mm	M63 x 1.5	20 mm	54 mm	8 pc	64 pc

Further technical details

Details	
Model	Straight
Revolving thread	False
Construction type	External thread
Material	PA-Blend

Cardboard packaging used is made from 100% waste paper and is fully recyclable, plastic packaging is fully recyclable.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt´s belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.