SLUG SPLITTER® punch system (stainless steel)



- Special alloy for maximum service life
- Split slugs fall free and can be disposed of easily

Suitable for

- Stainless steel (V2A), mild steel (St37), plastic and aluminium up to 3.5 mm thick

Operation

- Hydraulic

Predrilling


- Draw stud 11.1 mm dia., pilot drill 12.7 mm diameter 50344102
  draw stud 19.0 mm dia., pilot drill 20.5 mm diameter 50344030

Scope of supply

- Complete system including punch and die

Additional information

- * = Slug Splitter SC® - self-centring

Punch size			Max. Material thickness	Individual parts for manual operation		Draw studs	Complete unit
True dimension	Standard size						
mm	Pg	ISO	mm (V2A)	Punch	Die	Pump, hand and battery powered	Part No.
15.2	Pg 9		2.5	50311174	50311263	50294512	**50069519**
16.2		ISO 16	2.5	50045997	50045989	50294512	**50069527**
18.6	Pg 11		2.5	50311190	50311280	50294512	**50069535**
20.4	Pg 13	ISO 20	2.5	50311204	50311298	50294512	**50069543**
22.5	Pg 16		3.5	50281542	50281550	50294512	**50069551**
25.4		ISO 25	3.5	50046020	50046012	50294512	**50069560**
28.3	Pg 21		3.5	50281569	50281577	50294520	**50069578**
30.5			3.5	50364901	50364898	50294520	**50069586**
32.5		ISO 32	3.5	50046055	50046039	50294520	**50069594**
34.6			3.5	50281585	50281593	50294520	
37.0	Pg 29		3.5	50311220	50311352	50294520	**50069608**
40.5		ISO 40	3.5	50046080	50046071	50294520	**50069616**
43.2			3.5	50281607	50281615	50294520	
47.0	Pg 36		3.5	50311239	50311310	50294520	**50069624**
49.6			3.5	50281623	50281631	50294520	
50.8		ISO 50	3.5	50046110	50046098	50294520	**50069632**
54.0	Pg 42		3.5	50311247	50311328	50294520	**50069640**
60.0	Pg 48		3.5	50311255	50311336	50294520	**50069659**
61.5			3.5	50281658	50281666	50294520	
64.0		ISO 63	3.5	50046144	50046136	50294520	**50069667**