Ring terminals - Insulated



Scan this QR code for article numbers, current prices and stock information and to order directly.

Technical specifications

Brand	: WKK
Crimp terminal type	: Ring terminals
Maximum electrical voltage	: 600 V max.
Operating temperature (°C)	: -10 °C up to +75 °C
Insulation material	: PVC (vinyl)
Connector material	: Tin plated copper
Approvals	: RoHS

Type no.	Color	Wire range (mm²)	AWG	Hole (mm)	Overall length (mm)	PU (pcs.)
R 3.2 r	Red	0.5 ~ 1.5	22 ~ 16	3.2	18	100
R 3.7 r	Red	0.5 ~ 1.5	22 ~ 16	3.7	20	100
R 4.3 r	Red	0.5 ~ 1.5	22 ~ 16	4.3	20	100
R 5.3 r	Red	0.5 ~ 1.5	22 ~ 16	5.3	21	100
R 6.4 r	Red	0.5 ~ 1.5	22 ~ 16	6.4	27	100
R 8.4 r	Red	0.5 ~ 1.5	22 ~ 16	8.4	27	100
R 10.5 r	Red	0.5 ~ 1.5	22 ~ 16	10.5	31	100
R 3.7 b	Blue	1.5 ~ 2.5	16 ~ 14	3.7	20	100
R 4.3 b	Blue	1.5 ~ 2.5	16 ~ 14	4.3	22	100
R 5.3 b	Blue	1.5 ~ 2.5	16 ~ 14	5.3	22	100
R 6.4 b	Blue	1.5 ~ 2.5	16 ~ 14	6.4	27	100
R 8.4 b	Blue	1.5 ~ 2.5	16 ~ 14	8.4	27	100
R 10.5 b	Blue	1.5 ~ 2.5	16 ~ 14	10.5	31	100
R 3.7 g	Yellow	4.0 ~ 6.0	12 ~ 10	3.7	23	100
R 4.3 g	Yellow	4.0 ~ 6.0	12 ~ 10	4.3	27	100
R 5.3 g	Yellow	4.0 ~ 6.0	12 ~ 10	5.3	27	100
R 6.4 g	Yellow	4.0 ~ 6.0	12 ~ 10	6.4	30	100
R 8.4 g	Yellow	4.0 ~ 6.0	12 ~ 10	8.4	35	100
R 10.5 g	Yellow	4.0 ~ 6.0	12 ~ 10	10.5	35	100



WKK FIXATION MATERIALS
+31(0)13 571 21 71
sales@wkk-europe.com
www.wkk-europe.com