Bullet disconnectors - Insulated - Male



Technical specifications

Brand	: WKK
Crimp terminal type	: Bullet disconnectors male
Maximum electrical voltage	: 300 V max.
Operating temperature (°C)	: -10 °C up to +75 °C
Insulation material	: PVC (vinyl)
Connector material	: Tin plated brass
Approvals	: RoHS

Scan this QR code for article numbers, current prices and stock information and to order directly.

Type no.	Color	Wire range (mm²)	AWG	Diameter connector (mm)	Packing (pcs)
Kog m 4 r	Red	0.5 ~ 1.5	22 ~ 16	4	100
Kog m 4 b	Blue	1.5 ~ 2.5	16 ~ 14	4	100
Kog m 5 b	Blue	1.5 ~ 2.5	16 ~ 14	5	100
Kog m 5 g	Yellow	4.0 ~ 6.0	12 ~ 10	5	100

Diameter connector



Bullet disconnectors - Insulated - Female



Technical specifications

Brand	: WKK
Crimp terminal type	: Bullet disconnectors female
Maximum electrical voltage	: 300 V max.
Operating temperature (°C)	: -10 °C up to +75 °C
Insulation material	: PVC (vinyl)
Connector material	: Tin plated brass
Approvals	: RoHS

Scan this QR code for article numbers, current prices and stock information and to order directly.

Type no.	Color	Wire range (mm²)	AWG	Diameter connector (mm)	PU (pcs.)
Kog v 4 r	Red	0.5 ~ 1.5	22 ~ 16	4	100
Kog v 4 b	Blue	1.5 ~ 2.5	16 ~ 14	4	100
Kog v 5 b	Blue	1.5 ~ 2.5	16 ~ 14	5	100
Kog v 5 g	Yellow	4.0 ~ 6.0	12 ~ 10	5	100