Metal cable glands & accessories - Metric

Brass EMC cable glands - Metric - IP68 or IP69K



Scan this QR code for article numbers, current prices and stock information and to order directly.

Technical specifications

Brand	: Jacob
Material	: Brass CuZn39Pb3, nickel-plated
Connecting thread	: Metric (EN 60423)
Temperature range	: -20 °C up to +100 °C
Protection grade	: IP68 – 5 bar / IP69K (tested for M12 - M25, M50, M63)
Approvals:	: UL, CSA, DNV

Art. no.	Connecting thread	Cable diameter (mm)	Thread length (mm)	PU (pcs.)
50.612 M/EMV	M12 x 1.5	3.0 - 6.0	5	100
50.612 M/EMV/L	M12 x 1.5	3.0 - 6.0	10	100
50.616 M/EMV*	M16 x 1.5	5.0 - 9.0	5	100
50.616 M/EMV/L*	M16 x 1.5	5.0 - 9.0	10	100
50.620 M/EMV*	M20 x 1.5	9.0 - 13.0	6	100
50.620 M/EMV/L*	M20 x 1.5	9.0 - 13.0	10	100
50.625 M/EMV*	M25 x 1.5	11.0 - 16.0	7	50
50.625 M/EMV/L*	M25 x 1.5	11.0 - 16.0	11	50
50.632 M/EMV*	M32 x 1.5	14.0 - 20.0	8	25
50.632 M/EMV/L*	M32 x 1.5	14.0 - 20.0	13	25
50.640 M/EMV*	M40 x 1.5	19.0 - 27.0	8	10
50.640 M/EMV/L*	M40 x 1.5	19.0 - 27.0	13	10
50.650 M/EMV*	M50 x 1.5	24.0 - 35.0	9	5
50.650 M/EMV/L	M50 x 1.5	24.0 - 35.0	14	5
50.663 M/EMV*	M63 x 1.5	32.0 - 42.0	10	5
50.663 M/EMV/L	M63 x 1.5	32.0 - 42.0	14	5
50.663 M1/EMV	M63 x 1.5	38.0 - 48.0	10	5
50.663 M1/EMV/L	M63 x 1.5	38.0 - 48.0	14	5

From M40 x 1.5 available with O-ring
**= Available in EMVD version*

EMV version



EMVD version

