Disconnectors - Insulated - Female



Scan this QR code for article numbers, current prices and stock information and to order directly.

Technical specifications

Brand	: WKK
Crimp terminal type	: Disconnectors female
Maximum electrical voltage	: 300 V max.
Operating temperature (°C)	: -10 °C up to +75 °C
Insulation material	: PVC (vinyl)
Connector material	: Tin plated brass
Approvals	: RoHS

Type no.	Color	Wire range (mm²)	AWG	Tab (mm)	PU (pcs.)
Con vh 2.8 rs	Red	0.5 ~ 1.5	22 ~ 16	0.5 * 2.8	100
Con vh 2.8 r	Red	0.5 ~ 1.5	22 ~ 16	0.8 * 2.8	100
Con vh 4.8 rs	Red	0.5 ~ 1.5	22 ~ 16	0.5 * 4.8	100
Con vh 4.8 r	Red	0.5 ~ 1.5	22 ~ 16	0.8 * 4.8	100
Con vh 6.3 r	Red	0.5 ~ 1.5	22 ~ 16	0.8 * 6.3	100
Con vh 2.8 bs	Blue	1.5 ~ 2.5	16 ~ 14	0.5 * 2.8	100
Con vh 2.8 b	Blue	1.5 ~ 2.5	16 ~ 14	0.8 * 2.8	100
Con vh 4.8 bs	Blue	1.5 ~ 2.5	16 ~ 14	0.5 * 4.8	100
Con vh 4.8 b	Blue	1.5 ~ 2.5	16 ~ 14	0.8 * 4.8	100
Con vh 6.3 b	Blue	1.5 ~ 2.5	16 ~ 14	0.8 * 6.3	100
Con vh 6.3 g	Yellow	4.0 ~ 6.0	12 ~ 10	0.8 * 6.3	100

Disconnectors - Fully insulated - Female



Scan this QR code for article numbers, current prices and stock information and to order directly.

Technical specifications

Brand	: WKK
Crimp terminal type	: Disconnectors female
Maximum electrical voltage	: 300 V max.
Operating temperature (°C)	: -10 °C up to +75 °C
Insulation material	: PVC (vinyl)
Connector material	: Tin plated brass
Approvals	: RoHS

Type no.	Color	Wire range (mm²)	AWG	Tab (mm)	PU (pcs.)
Con vv 2.8 rs	Red	0.5 ~ 1.5	22 ~ 16	0.5 * 2.8	100
Con vv 2.8 r	Red	0.5 ~ 1.5	22 ~ 16	0.8 * 2.8	100
Con vv 4.8 rs	Red	0.5 ~ 1.5	22 ~ 16	0.5 * 4.8	100
Con vv 4.8 r	Red	0.5 ~ 1.5	22 ~ 16	0.8 * 4.8	100
Con vv 6.3 r	Red	0.5 ~ 1.5	22 ~ 16	0.8 * 6.3	100
Con vv 2.8 bs	Blue	1.5 ~ 2.5	16 ~ 14	0.5 * 2.8	100
Con vv 2.8 b	Blue	1.5 ~ 2.5	16 ~ 14	0.8 * 2.8	100
Con vv 4.8 bs	Blue	1.5 ~ 2.5	16 ~ 14	0.5 * 4.8	100
Con vv 4.8 b	Blue	1.5 ~ 2.5	16 ~ 14	0.8 * 4.8	100
Con vv 6.3 b	Blue	1.5 ~ 2.5	16 ~ 14	0.8 * 6.3	100
Con vv 6.3 g	Yellow	4.0 ~ 6.0	12 ~ 10	0.8 * 6.3	100