



Data sheet | Item number: 224-112

2-conductor lighting connector; Standard version; Continuous service  
temperature 105°C

[www.wago.com/224-112](http://www.wago.com/224-112)



## Data Electrical data

Rated voltage (II / 2)	400 V
Rated impulse voltage (II / 2)	4 kV
Rated current	24 A
Legend (ratings)	(II / 2) ▲ Overvoltage category II / Pollution degree 2

## Connection data

Connection type (1)	Installation side:
Connection technology	PUSH WIRE®
Number of connection points (connection type)	0
Actuation type	Push-in
Connectable conductor materials	Copper
Solid conductor	1 ... 2.5 mm² / 14 ... 12 AWG
Strip length	9 ... 11 mm / 0.35 ... 0.43 Inch
Connection type (2)	Lighting side:
Connection technology 2	CAGE CLAMP®
Number of connection points (connection type 2)	1
Solid conductor (2)	0.5 ... 2.5 mm² / 20 ... 16 AWG
Fine-stranded conductor (2)	0.5 ... 2.5 mm² / 20 ... 16 AWG
Total number of connection points	3
Total number of potentials	1
Type of wiring	Side-entry wiring

## Geometrical Data

Width	9.5 mm / 0.374 Inch
Height	15.5 mm / 0.61 Inch
Depth	20.5 mm / 0.807 Inch

## Material Data

Color	white
Fire load	0.046 MJ
Weight	2.066 g

## Environmental Requirements

Continuous operating temperature up to	105 °C
--	--------

## Commercial data

Packaging type	BOX
Country of origin	CH
GTIN	4044918583596
Customs Tariff No.	85369010000
Product Group	7 (Push Wire Conn.)

## Country specific Approvals

Logo	Approval	Certificate name
	CSA DEKRA Certification B.V.	1053495
	VDE VDE Prüf- und Zertifizierungsinstitut	40022792

## Ship Approvals

Logo	Approval	Certificate name
	ABS American Bureau of Shipping	15-HG1419918-PDA
	BV Bureau Veritas S.A.	11914/C0 BV
	LR Lloyds Register	04/20013 (E4)

#### UL-Approvals

Logo	Approval	Certificate name
 CCA	UL UL International Germany GmbH	E69654
	UL UL International Germany GmbH	CCA-DK No. 2527

Subject to changes.